


FM300 Desktop Formaldehyde (CH₂O or HCHO) Monitor

- Insulation/Plywood/Fiberboard - Shampoos



Measures Formaldehyde concentration, Air Temperature and Humidity with user-settable audible alarm (0.08ppm default). Excellent for monitoring indoor air quality of areas affected by formaldehyde gas.

Applications:

Formaldehyde is used in the manufacture of many industrial and consumer goods. Emissions from some of these items can rise when moisture and heat increase. These emissions are a contributing factor to Sick Building Syndrome, which may lead to itchy eyes and throat, as well as headaches and dizziness.

- Paint
- Timber Paneling/Particleboard Soap Bars/Body Wash
- Cosmetics
- Lotions - Toothpaste



EXTECH

Features

- Simultaneously displays Formaldehyde concentration, Air Temperature, and Relative Humidity readings with date (Year, Month, Day) and time
- Visibly bright LED (green & red) and three facial icons indicate indoor CH₂O warning level
- Audible beeping alarm default at 0.08ppm (adjustable)
- Designed with Electrochemical CH₂O sensor
- Min/Max CH₂O value recall function
- · Calculates statistical weighted averages of TWA (8-hour Time Weighted Average) and STEL (15-minute Short Term Exposure Limit)
- CH₂O Calibration function in fresh air

- Internal memory for manually storing up to 99 readings with recall function
- Complete with Universal AC adapter (100V-240V) and multiple plug types (US, EU, UK, AUS)

E	>0.8ppm CH ₂ O
	>0.08ppm, <0.80ppm CH ₂ O
•	<0.08ppm CH ₂ O

Three facial icons indicating CH₂O concentration level for indoor air quality

Specifications	Range	Resolution	Basic Accuracy
Formaldehyde (CH ₂ O or HCHO)	0.00 to 5.00ppm	0.01ppm	±5%
Air Temperature	32 to 122°F (0 to 50°C)	0.1°F/°C	±2°F/1°C
Humidity	10 to 90%RH	0.1%RH	±5%RH
Dimensions	6.1 x 3.4 x 3.2" (155 x 87 x 81mm)		
Weight	5.8oz (165g)		

Ordering

FM300..... Desktop Formaldehyde Monitor

 ϵ